

NEW

YM225 YM238

	YM225	YM238
Ideal Acreage	25-45 acres	
Engine HP	24.4 HP	38.2 HP
Loader Lift Capacity	1,500 LBS.*	
Transmission	Synchronized Reverser Transmission (SRT)	
*lift capacity to maximum height at pivot pin		



The YM2 line offers Yanmar craftsmanship and engineering in a compact, agile body. Enjoy the highest lift capacity in this horsepower range, and the ergonomic design and efficiency features you deserve.

For those who need that extra burst of power, the YM238 includes Turbo!



POWERFUL PERFORMANCE

True to Yanmar's unmatched reputation for reliability, the YM2 series engines are not only tough enough for all your tasks, they're the best in class for fuel efficiency and the cleanest in the category. The YM2 series is truly the star of the next generation of compact tractors.

OUTSTANDING CRAFTSMANSHIP

Built for superior durability and reliability, and surpassing industry standards at every turn, it's designed to stand the test of time. Enjoy a legacy your family will value for generations.

INNOVATIVE COMFORT & DESIGN

From the ergonomically designed, extra-comfortable seat to the intuitive operator station, every detail is crafted to elevate your everyday.



NEW

**YM225
YM238**
TRACTOR



TURBO ENGINE AVAILABLE ON YM238.



INFORMATIVE DISPLAY PANEL.



INNOVATIVE COMFORT & DESIGN.

SPECIFICATIONS

	YM225	YM238
Ideal Acreage		
Engine HP	24.4 HP (18.2 kW)	38.2 HP (28.5 kW)
Transmission	Synchronized Reverser Transmission (SRT)	

WARRANTY COVERAGE

Tractor* 24 months or 2,000 hours (whichever comes first)

*for non-commercial, home and residential use only

POWERTRAIN

Engine Manufacturer		
Engine Gross Power	24.4 HP (18.2 kW)	38.2 HP (28.5 kW)
PTO Power	18.5 HP (13.8 kW)	31.9 HP (23.8 kW)
Rated Engine Speed	2,400 RPM	2,600 RPM
Clutch	Dry Single Plate	

CAPACITIES

Fuel Tank	40.0 L
-----------	--------

DRIVETRAIN

Transmission Type	Synchronized Reverser Transmission (SRT)
Rear Differential Lock	Foot Pedal Engagement
2WD/4WD Engagement	Selectable
PTO Type	Transmission Driven with Overrunning Clutch
Rear PTO Speed	540 RPM @ 2,360 rpm

HYDRAULICS

Pump Capacity (Steering)	14.5 L/min	15.7 L/min
Pump Capacity (Implement)	23.8 L/min	25.8 L/min
3-Point Hitch	Category 1	
3-Point Lift Capacity (Std.)	1,000 kgf	
3-Point Lift Capacity at 24" (61 cm)	730 kgf	
Remote Valve	Optional	
3rd Function Valve	Optional	

DIMENSIONS AND WEIGHT

Fuel tank capacity (l)	40L	40L
Overall Length (with 3P) (mm)	2959	2959
Overall Width (mm)	1360	1360
Overall Height (CANOPY) (mm)	2200	2200
Wheelbase (mm)	1650	1650
Min. ground clearance (mm)	350	350
Track Settings (Front) mm	1071mm ± 15 (Tyre 7.00-16)	1071mm ± 15 (Tyre 7.00-16)
Track Settings (Rear) mm	1080mm ± 15 (Tyre 11.2-24)	1080mm ± 15 (Tyre 11.2-24)
Weight (with mass) (kg) (Without Ballast Weights)	1290	1290
Min. turning radius (m) With brakes	3.1	3.1

TRACTOR LEVEL

Roll Over Protection	Rear ROPS, Rear ROPS with Canopy & Lights
Canopy/Cabin	OP: Front ROPS Canopy, HVAC

TIRE DETAILS

Agricultural Bias	7x16, 11.2x24
Agricultural Radial	200/70 R16 & 320/70 R20
Industrial	27*8.5-15 & 380/70-19.5
Turf	25*8.5-14 & 345/80-16

YANMAR STAM B.V.

STAM B. V. Netherlands | E: sales@yanmarstambv.nl | www.yanmarstambv.com